

RoHS Compliant

REVISIONS

REV.	DESCRIPTION	DATE	DESIGN

■ Specifications :

- Voltage rating: 50V AC / DC
- Current rating: 1.5A AC / DC
- Withstanding voltage: 500V AC/minute
- Temperature range: -25°C~+85°C
- Insulation resistance: ≥100MΩ
- Contact resistance: ≤20MΩ
- After environmental testing: ≤40MΩ

Poles	Dimensions(mm)		
	A	B	C
02	1.20	2.60	3.10
03	2.40	3.80	4.30
04	3.60	5.00	5.50
05	4.80	6.20	6.70
06	6.00	7.40	7.90
07	7.20	8.60	9.10
08	8.40	9.80	10.30
09	9.60	11.00	11.50

1202H-XXS-P0

PA66 UL94V-0

1202T-S

Part No.

Material

Suitable Terminal

Bestcreate Technology Limited

TOLERANCES UNLESS OTHERWISE SPECIFIED:

.X	±	0.30	X'	±	3'
.XX	±	0.20	.X'	±	2'
.XXX	±	0.10	.XX'	±	1'

Website: www.bsc-elec.com

Email: bestcreate@bsc-elec.com

DESIGN:

DATE:

I. L.

2017. 3. 1

CHECKED:

DATE:

C. W.

2017. 3. 1

APPROVED:

DATE:

C. W.

2017. 3. 1

TITLE:

1. 20MM Housing

MATERILA:

PART NO:

1202H-XXS-P0

SIZE:

A4

FINSH:

DWG NO:


1202H-XXS-P0

REV: A

UNIT mm

SCALE 1=1

QUALITY SYMBOLS



1

2

3

4

5

6

7

8