

RoHS Compliant

REVISIONS

REV.	DESCRIPTION	DATE	DESIGN

SPECIFICATIONS:




- 1.VOLTAGE/CURRENT RATING: 30V/AC, DC,0.3A;
- 2.WITHSTANDING VOLTAGE: 100V AC/ONE MINUTE;
- 3.INSULATION RESISTANCE: 50M Ω MIN/100V DC.;
- 4.CONTACT RESISTANCE: 90m Ω MAX./1mA,20mV AC,1KHz;
- 5.DURABILITY: 30 CYCLES;
- 6.OPERATING TEMPERATURE RANGE: -35° C to 85° C.

MATERIAL:



- 1.INSULATOR: LCP UL 94V-0 BLACK;
- 2.TERMINAL: PHOSPHOR BRONZE;

PLATING:

- 1.TERMINAL: CONTACT AREA: GOLD 0.05 μ m"MIN.
SMT LEAD: GOLD 0.025 μ m" MIN.
UNDERPLATING: NICKEL 1 μ m" MIN.



RECOMMENDED PCB LAYOUT



PIN NO.	DIM A	DIM B	DIM C	DIM D
10	4.60	1.60	3.55	1.00
12	5.00	2.00	3.95	1.00
20	6.60	3.60	5.55	1.00
24	7.40	4.40	6.35	1.20
30	8.60	5.60	7.55	1.50
34	9.40	6.40	8.35	1.50
40	10.60	7.60	9.55	3.20
50	12.60	9.60	11.55	3.20
60	14.60	11.60	13.55	3.20
70	16.60	13.60	15.55	3.20
80	18.60	15.60	17.55	3.20
90	20.60	17.60	19.55	3.20
100	22.60	19.60	21.55	3.20
120	26.60	23.60	25.55	3.20

Bestcreate Technology Limited

TOLERANCES UNLESS OTHERWISE SPECIFIED:

.X	$\pm$ 0.30	.X"	$\pm$ 3"
.XX	$\pm$ 0.20	.X"	$\pm$ 2"
.XXX	$\pm$ 0.10	.X"	$\pm$ 1"

Website: www.bsc-elec.com
Email: bestcreate@bsc-elec.com

DESIGN:

DATE:

CHECKED:

DATE:

APPROVED:

DATE:

TITLE:

BTB SOCKET P0.40 H1.5

MATERIAL:

PART NO:

SIZE:

FINISH:

DWG NO:

REV:

A


UNIT

mm

SCALE

1=1

QUALITY
SYMBOLS



1

2

3

4

5

6

7

8