

RoHS Compliant

焊脚尺寸以顺畅过孔规为准

REVISIONS

REV.	DESCRIPTION	DATE	DESIGN

NOTES

MATERIAL

1. HOUSING MATERIAL : THERMO PLASTICS UL94V-0.
2. CONTACT MATERIAL : PHOSPHOR BRONZE T=0.25mm.
3. PLATING : GOLD FLASH PLATED ON CONTACT, TIN PLATED ON SOLDER, OVER NICKEL.
4. SHIELD : SUS T=0.2mm. WITH NICKEL PLATED.

ELECTRICAL

1. VOLTAGE RATING : 125 VAC RMS.
2. CURRENT RATING : 1.5 AMP.
3. CONTACT RESISTANCE : 40 MILLIOHMS MAX.
4. INSULATION RESISTANCE : 500 MEGOHMS MIN @ 100V DC .
5. DIELECTRIC DIELECTRIC RESISTANCE : 500V DC RMS 50Hz. 1MIN.

MECHANICAL

1. DURRABILITY : 750 CYCLES MIN.
2. MATING/UNMATING FORCE : 2.24 KG.F MAX.

ENVIRONMENTAL:

1. STORAGE : -40℃~+85℃.
2. OPERATION : 0° C TO 70° C.

YELLOW 9+ 10- LEFT	100兆	1000兆
	8	8
GREEN 11+ 12- RIGHT	7	7
	6	6
	5	5
	4	4
	3	3
	2	2
	1	1
	PIN序 说明	PIN序 说明

PART NO. INFORMATION

RJ01- X 1 B X - 139

CONTACT PLATED

- 1: G/F
- 2: AU 3U"
- 3: AU 6U"
- 4: AU 10U"
- 5: AU 15U"
- 6: AU 30U"

PACKAGE
R: TAPE REEL
T: TRAY

LED COLOR
1.L-YELLOW R-GREEN

HOUSING
B:LCP BLACK

Bestcreate Technology Limited

TOLERANCES UNLESS OTHERWISE SPECIFIED:

.X	±	0.35	X.*	±	3"
.XX	±	0.25	.X.*	±	2"
.XXX	±	0.15	.XX.*	±	1"

Website:www.bsc-elec.com

Email:bestcreate@bsc-elec.com

DESIGN:

DATE:

I. L

2017. 3. 1

CHECKED:

DATE:

C. W

2017. 3. 1

APPROVED:

DATE:

C. W

2017. 3. 1

TITLE:

RJ45 9.8H MID-MOUNT 7.2 FEMALE CONNECTOR DIP TYPE

MATERILA:

PART NO:

RJ01-X1BX-139

SIZE:

A4

FINSH:

DWG NO:

RJ01-X1BX-139

1 OF 1

REV:

A

UNIT

mm

SCALE

1=1

QUALITY

SYMBOLS

