	1	2	3	4	5	6	7	8	
	RoHS Compliant						REVISIONS	;	
						REV.	DESCRIPTION	DATE	DESIGN
A		10.44 9.04 8.34 ^{+0.06} A1 A1 B12 B12 B12 B1	10.00 23.00 美前塞示意图			2.VOLTAG 3.VBUS & SHIELD LLCR M 4.INSULA 5.DIELEC 6.LNSERT 7.UNMATI 8.DURABI 9.OPERA 10.THE PI BE MA	ATION: NT RATING: 3.0 A BE RATING: 3.0 V GND PINS AND OTHER PINS: 4 b: 50mΩ/MAX IAX. CHANGE OF ALL PINS: 10Ω TION RESISTANCE: 100MΩ MIN TRIC WITHSTAND VOLTAGE,AC TON FORCE: 0.5~2.0kgf ING FORCE: 0.8~2.0kgf LITY: 10000 CYCLES TING TEMPERATURE: -35°C~+8 EAK TEMPERATURE: -35°C~+8 EAK TEMPERATURE ON THE BC INTAINED FOR 10 SECONDS AT PROOF:IP-X7.	0m I 000V FOR 1MIN 5°C DARO SHALL	UTE F
C	6.80 6.80 1.00 1.00 1.00					WITH O-RING	PIN NUMBER A1 A4 A5	PIN ASSIGNMENTS SIGNAL NAME PIN NUMBER GND B12 VBUS B9 CC1 B8	R SIGNAL NAME GND VBUS SBU2
				PART NO. INFORMATIC	N		A6 A7	DP1 B7 DN1 B6	DN2 DP2
	-	B12 B12 B1 B1 B1 B1 B1 B1 B1 B1 B1 B1		PORT TYPE C: TYPE C GENDER F: FEMALE M: MALE CONTACT PLATED 1: GOLD FLASH	X X 5 R - W029 PACKAGE R: TAPE REEL HOUSING COLOR 2: WHITE 5: BLACK 9: NATURE	TABLE NO 1 2	A8 A9 A12 PART Q'TY SHELL 1 ZINC ALLOG,	SBU1 B5 VBUS B4 GND B1 Material NI30u"Min PLATED Au3u"/NI30u"PLATED	CC2 VBUS GND
D		A12 - A12		2: GOLD 3U" 3: GOLD 5U" 4: GOLD 10U" 5: GOLD 15U" 6: GOLD 30U"	HOUSING MATERIAL A: LCP B: PBT C: PA9T D: PA6T E: PA46 F: PA66	3 4 5 6 DATE:	MID PLATE 1 SUS301,N0 PLA HOUSING 1 LCP(E130i) CAP 1 LCP UL94 V	TING UL94 V-0 BLACK	
	Bestcreat	te Technology L			$\begin{array}{c} \text{ISE SPECIFIED:} \\ \underline{\pm} 5^{*} \\ \underline{\pm} 2^{*} \\ \underline{\pm} 1^{*} \end{array} \begin{array}{c} \text{OHECKED:} \\ \text{C.W} \end{array}$	DATE:	IPX7 Waterproof USB TYPE (Vertical DIP type,L=6.8mm MATERILA: PART NO:		SIZE: A4
	REV: UNIT m	m SCALE QUALITY 1=1 SYMBOLS	Web	osite:www.bsc-elec.com	APPROVED:	DATE:	FINSH: DWG NO:	U06-CFXX5R-W029	1 OF 3
	1 M		· [Lill	ail:bestcreate@bsc-ele		7	7	U06-CFXX5R-W029	
	1	2	3	4	5	6	/	8	

	1	2	3	4	5	6	7	8
RoHS	Compliant						REVISIONS	
						REV.	DESCRIPTION	DATE DESIGN
A	20 Min /1 5M							A
	³⁰ Min/1.5M IP-X7		9.18					
				3.40				
						率科 开1	化参考尺寸(只供参	老)
B						组袋外疗	壱时需要打环保润 滑	ř油 B
			10.7			4.90		
				SOMin SOMin				
				● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ●				
				三三三十二十二、「「「「」」を「「」」を見てて、「」」を見てて、「」」を見てて、「」」を見てて、「」」を見てて、「」」を見てて、「」」を見ている。				
				(建设 》				
D				1				D
		TOLERANCES UNLESS OTHERWISE SPECIFIED: TOLERANCES UNLESS OTHERWISE SPECIFIED: TOLERA						
	stcreate	Technolo	ogy Limited	.X ± 0.20 X.* .XX ± 0.15 .X*		D: DATE:	Vertical DIP type,L=6.8mm	
				.XXX ± 0.10 .XX*	$\begin{array}{c c} \pm & 2 \\ \hline \pm & 1 \end{array}$ C. W		MATERILA: PART NO: U	06-CFXX5R-W029
REV:	UNIT	SCALE 1=1	QUALITY SYMBOLS	Website:www.bsc-elec.com	APPROV C. W	ED: DATE:	FINSH: DWG NO:	
	1	2	311111111111111111111111111111111111111	Email:bestcreate@bsc-elec 4	<u>5</u>	6		06-CFXX5R-W029 2 OF 3
	1	Ľ	3	4	J	D	/	0

	1	2	3	4	5	6	7	8	
	RoHS Complian	nt				REV.	REVISIONS	DATE	DEDIONI
А		REEL OFF SECTION (14 POCKETS)	700PCS PUL	L OUT DIRECTION (14 POCKETS)	PAPER BOARD		FOLDER PAPER BOARD		DESIGN
В			165°~180° PEELING ANGLE PULL OUT DIRECTION		EEL AND TAPE		CARTON	>	_
С		REEL OFF OFF DIRECTION		PULL OUT DIRECTION		CONNECTOR (PCS)		RTON 5000	-
	Bestcre			.XXX ± 0.10 .XX*	± 5' ± 2' ± 1' APPROVED:	DATE: DATE: DATE:	FINSH: DWG NO:		INECTOR SIZE: A4 3 OF 3