

RoHS Compliant

REVISIONS

REV.	DESCRIPTION	DATE	DESIGN

NOTE:

- MATERIALS AND FINISHED
INSULATOR : PBT+30% GF UL 94V-0,
SHELL : STEEL, NI FINISHED
CONTACT MATERIAL : BRASS, SELEVITE GOLD FINISHED
RIVETED INSERT: BRASS MATERIAL ,TIN FINISHED
WITH #4-40 THREADED ASSEMBLED
- ELECTRICAL CHARACTERISTICS
CURRENT RATING : 3.0 AMP DC
VOLTAGE RATING: 250 V DC
CONTACT RESISTANCE :30 MILLIOHMS MAX.
DIELECTRIC WITHSTANDING VOLTAGE : 1000 V AC MIN.
INSULATION RESISTANCE : 1000 MEGAOHMS MIN.
- ENVIRONMENTAL
OPERATING TEMPERATURE: -55°C ~ +85°C
STORAGE TEMPERATURE:-55°C ~ +105°C
- HOW TO ORDER:

DL304X-30XX5X1-XX530

Male+Female
HDR+HDR

2: DimX/Y=19.05/31.60
1: DimX/Y=15.88/28.43

24: H15Pin+H15Pin

S:Selevite Gold Bright TIN
M:Selevite Gold Matte TIN

1:G/F 5: 5u"
2:2u" 6: 10u"
3:3u" 7: 15u" 9: 1u"

5. Full Ni(Shell)

O: RoHS
9: Lower-HDR 8.89(short pin9)
3: Lower-HDR 8.89

6: Quad Arrowhead Boardlock (8.89x8.85)
5: Quad Arrowhead Boardlock (9.5x8.18)
2: Quad Arrowhead Boardlock (8.89x8.8L)

K: 5.8*12.8 Hexagonal Screw(iron)
J: 5.8*12.8 Hexagonal Screw(copper)
6: 4.8*11.8 Hexagonal Screw(iron)
5: 4.8*11.8 Hexagonal Screw(copper)
O: W/O Screw

C: Attach screw type
B: Ass'y screw type
A: No screw type

1: PBT+PBT
2: Upper-Black, Lower-Blue
1: All Black

P.C.B EDGE
RECOMMENDED P.C.B LAYOUT