

RoHS Compliant

REVISIONS

REV.	DESCRIPTION	DATE	DESIGN

NOTE:

1.MATERIAL:

- 1.1 Housing : High Temperature Thermoplastics.BK.UL94 V-0.
1.2 Contact:Copper Alloy.Flash Gold Plating Overall.
1.3 Shell :Copper Alloy.Nickel Plating Overall.

2.ELCTRICAL PERFORMANCE :

- Voltage Current Rating : 1.5 AMP. 30V AC.
Insulation Resistance : 1000M Ω Min.
Contact Resistance : 40 m Ω Max.
Dielectric Withstanding Voltage : 500V AC.

- 3.Temperature Range : -45°C to +85°C.

PART NO. INFORMATION


RJHD01- X 5 0 X - 008

CONTACT PLATED

- 1: G/F 2: AU 3U"
3: AU 6U" 4: AU 15U"
5: AU 30U"

PACKAGE

- R: TAPE REEL
T: TRAY



RECOMMENDED P.C.B LAYOUT
TOP VIEW (COMPONENT SIDE)

Bestcreate Technology Limited

TOLERANCES UNLESS OTHERWISE SPECIFIED:

.X	±	0.35	X'	±	3'
.XX	±	0.25	.X'	±	2'
.XXX	±	0.15	.XX'	±	1'

Website: www.bsc-elec.com

Email: bestcreate@bsc-elec.com

DESIGN: DATE:

I. L. 2017. 3. 1

CHECKED: DATE:

C. W. 2017. 3. 1

APPROVED: DATE:

C. W. 2017. 3. 1

TITLE:

RJ45 WITH HDMI TYPE ,WITH LEDS

MATERILA:

PART NO: RJHD01-X50X-008

SIZE: A4

FINSH:

DWG NO: RJHD01-X50X-008

REV: A


UNIT

mm

SCALE

1=1

QUALITY
SYMBOLS



1

2

3

4

5

6

7

8