






RoHS Compliant

REVISIONS			
REV.	DESCRIPTION	DATE	DESIGN



PCB LAYOUT/TOP VIEW

NOTES:

ELECTRICAL:

- 1. VOLTAGE RATING : 125 VAC RMS.
- 2. CURRENT RATING : 1.5 AMP.
- 3. CONTACT RESISTANCE : 40 MILLIOHMS MAX.
- 4. INSULATION RESISTANCE : 500 MEGOHMS MIN @ 100 VDC.
- 5. DIELECTRIC STRENGTH : 500 VDC RMS 50Hz or 60Hz, 1MIN.

MECHANICAL:

- 1. HOUSING & INSERT MATERIAL : PBT/PA66 UL94V-0.
- 2. CONTACT MATERIAL : Ø0.46 PHOSPHOR BRONZE GOLD PLATING OVER NICKEL.
- 3. MATING/UNMATING FORCE : 2.24KG. F MAX.
- 4. OPERATING LIFE : 750 CYCLES MIN.

ENVIRONMENTAL:

- 1. STORAGE : -40°C~+85°C.
- 2. OPERATION : -40°C~+85°C.

PART NO. INFORMATION

RJ01- X 5 X T - 106

CONTACT PLATED
 1: G/F 2: AU 3U"
 3: AU 6U"

PACKAGE
 T: TRAY

HOUSING:
 1:PBT BLACK
 2:PBT YELLOW

Bestcreate Technology Limited

TOLERANCES UNLESS OTHERWISE SPECIFIED:			
.X	± 0.35	.X'	± 3'
.XX	± 0.25	.X''	± 2'
.XXX	± 0.15	.X'''	± 1'

Website: www.bsc-elec.com
 Email: bestcreate@bsc-elec.com

DESIGN:	DATE:
I. L	2017. 3. 1
CHECKED:	DATE:
C. W	2017. 3. 1
APPROVED:	DATE:
C. W	2017. 3. 1

TITLE: 5921 1X4 RJ45 CONNECTOR DIP TYPE		
MATERILA:	PART NO: RJ01-X5XT-106	SIZE: A4
FINSH:	DWG NO: RJ01-X5XT-106	

REV: A	UNIT mm	SCALE 1=1	QUALITY SYMBOLS
--------	---------	-----------	-----------------