

1

2

3

4

5

6

7

8

RoHS Compliant

REV.

DESCRIPTION

DATE

DESIGN

A

B

C

D

19.5

11.4

10

20.9

39.9

20

19.9

10

11.4

0.2

39.5

0.2

8.0

7.7

WIRING TABLE

| P1 | P2 |
|----|----|
| 1 | 1 |
| 3 | 3 |
| 2 | 2 |
| 4 | 4 |
| 6 | 6 |
| 5 | 5 |
| 7 | 7 |
| 9 | 9 |
| 8 | 8 |
| 10 | 10 |
| 12 | 12 |
| 11 | 11 |
| 14 | 14 |
| 19 | 19 |
| 17 | 17 |
| 13 | 13 |
| 15 | 15 |
| 16 | 16 |
| 18 | 18 |
| 20 | 20 |
| 外壳 | 外壳 |

TEST CONDITION:

a.100% SHORT CIRCUIT/OPEN CIRCUIT TEST。

b.DC:300V AC:200V INSULATION RESISTANCE:10MΩ

c.CONDUCTOR RESISTANCE :≤5Ω

d.8K*4K 60HZ VEDIO AND AUDIO TEST。

| ITEM | MATERIAL | SPECIFICATION | UNIT | QTY |
|------|----------------|---|------|-----|
| 6 | PACKAGE | SELF SEAL ZIPPER PE BAG | pcs | 1 |
| 5 | PVC MATERIAL | 45P CAL65 N18P ENVIRONMENTAL MATERIAL | g | 6 |
| 4 | PE MATERIAL | PE LOW DENSITYPE INTERNAL MOLD MATERIAL | g | 3 |
| 3 | ALUMINUM SHELL | BLACK ALUMINUM SHELL20.9mm*10mm*11mm NETC LOGO | pcs | 2 |
| 2 | PCBA | 4 LAYER PCBA | pcs | 1 |
| 1 | CONNECTOR | DP 1.4 AF SPCC SHELL WITH GOLD PLATING,1U'ON CONTACT,STRADDLE MOUNT | PCS | 2 |

Bestcreate Technology Limited

REV: A

UNIT mm

SCALE 1=1

QUALITY SYMBOLS

TOLERANCES UNLESS OTHERWISE SPECIFIED:

| | |
|------------|-----------|
| X. ± 0.50 | X.* ± 5° |
| .X ± 0.30 | .X* ± 2° |
| .XX ± 0.10 | .XX* ± 1° |

Website:www.bsc-elec.com

Email:bestcreate@bsc-elec.com

DESIGN: I. L

DATE: 2017.3.1

CHECKED: C. W

DATE: 2017.3.1

APPROVED: C. W

DATE: 2017.3.1

TITLE: DP FEMALE TO DP FEMALE 8K ALUMINUM SHELL ADAPTER

MATERILA:

FINSH:

PART NO: DPFF8K-001

DWG NO: DPFF8K-001

SIZE: A4

1

2

3

4

5

6

7

8