

1

2

3

4

5

6

7

8

RoHS Compliant

REV.

DESCRIPTION

DATE

DESIGN

A

B

C

D

20.9

11.4

20.9

11

17

18.2

46.2

20.9

10

11.4

17

46

0.2

ALUMINUM

8.0

7.7

WIRING TABLE

P1	P2
1	1
3	3
2	2
4	4
6	6
5	5
7	7
9	9
8	8
10	10
12	12
11	11
14	14
19	19
17	17
13	13
15	15
16	16
18	18
20	20
外壳	外壳

TEST CONDITION:

a. 100% SHORT CIRCUIT/OPEN CIRCUIT TEST.

b. DC:300V AC:200V INSULATION RESISTANCE:10MΩ

c. CONDUCTOR RESISTANCE :≤5Ω

d. 8K*4K 60HZ VIDEO AND AUDIO TEST.

6	PACKAGE	SELF SEAL ZIPPER PE BAG	pcs	1
5	PVC MATERIAL	45P CAL65 N18P ENVIRONMENTAL MATERIAL	g	6
4	PE MATERIAL	PE LOW DENSITY INTERNAL MOLD MATERIAL	g	3
3	ALUMINUM SHELL	BLACK ALUMINUM SHELL 20.9mm*10mm*11mm NETC LOGO	pcs	2
2	PCBA	4 LAYER PCBA	pcs	1
1	CONNECTOR	DP 1.4 FEMALE SPCC SHELL WITH GOLD PLATING, 1U' ON CONTACT, STRADDLE MOUNT	PCS	2
ITEM	MATERIAL	SPECIFICATION	UNIT	QTY

Bestcreate Technology Limited

TOLERANCES UNLESS OTHERWISE SPECIFIED:

X.	±	0.50	X.	±	5°
.X	±	0.30	.X.	±	2°
.XX	±	0.10	.XX.	±	1°

Website:www.bsc-elec.com

Email:bestcreate@bsc-elec.com

DESIGN:

DATE:

2017.3.1

CHECKED:

DATE:

2017.3.1

APPROVED:

DATE:

2017.3.1

TITLE:

DP FEMALE TO FEMALE 8K ALUMINUM SHELL ADAPTER

MATERILA:

PART NO:

DPFF8K-002

SIZE:

A4

FINSH:

DWG NO:

DPFF8K-002

REV:

A

UNIT

mm

SCALE

1=1

QUALITY SYMBOLS

1

2

3

4

5

6

7

8