



RoHS Compliant

REVISIONS			
REV.	DESCRIPTION	DATE	DESIGN

NOTE:

- MATERIALS AND FINISHED
 INSULATOR : PBT GF30% UL 94V-0, BLACK,
 SHELL : STEEL, NI FINISHED
 CONTACT MATERIAL : BRASS, SELEVITE GOLD FINISHED
 RIVETED INSERT: BRASS MATERIAL ,NI FINISHED
 WITH #4-40 THREADED ASSEMBLED
- ELECTRICAL CHARACTERISTICS
 CURRENT RATING : 3 AMP
 VOLTAGE RATING: 300 V DC
 CONTACT RESISTANCE :20 MILLIOHMS MAX.
 DIELECTRIC WITHSTANDING VOLTAGE : 1000 V AC MIN.
 INSULATION RESISTANCE : 1000 MEGAOHMS MIN.
- ENVIRONMENTAL
 OPERATING TEMPERATURE: -55°C ~ +85°C
 STORAGE TEMPERATURE:-55°C ~ +105°C
- HOW TO ORDER:

DRF161-09XX5P-XXX10

- F: Female
- 1: Stamping forming
- 6: DR(10.2)
- 09: 9PIN 25: 25PIN
- 15: 15PIN 37: 37PIN
- G: Full Gold
- S: Selevite Gold Bright TIN
- 1:1u" 5: 5u"
- 2:2u" 6: 10u"
- 3:3u" 7: 15u" 8: 30u"
- 4: FULL Gold 5: FULL NI
- 0: RoHs
- 1:steel harpoon
- 2:copper harpoon
- 5: 4.8*11.8copper screws
- 6: 4.8*11.8steel screws
- J: 5.8*12.8copper screws
- K: 5.8*12.8steel screws
- A:No_screw type
- B:Assy screw type
- C:Attach screw type
- D:Fork Lock
- P: PBT A: PA9T
- B: Black G: Green

Bestcreate Technology Limited

TOLERANCES UNLESS OTHERWISE SPECIFIED:

.X	± 0.35	X.'	± 3'
.XX	± 0.25	.X'	± 2'
.XXX	± 0.15	.XX'	± 1'

Website:www.bsc-elec.com
 Email:bestcreate@bsc-elec.com

DESIGN:	DATE:
I.L	2017.3.1
CHECKED:	DATE:
C.W	2017.3.1
APPROVED:	DATE:
C.W	2017.3.1

TITLE: DR 10.2-09P FEMALE CONNECTOR		
MATERILA:	PART NO: DRF161.09XX5P.XXX10	SIZE: A4
FINSH:	DWG NO: DRF161.09XX5P.XXX10	

REV: A	UNIT mm	SCALE 1=1	QUALITY SYMBOLS
-----------	------------	--------------	-----------------